

NiTEO PRODUCTS		Page: 1
SAFETY DATA SHEET		Revision Date: 01/26/2016
		Print Date: 2/21/2017
		SDS Number: 000000264507
Pyroil™ POWER STEERING FLUID		Version: 1.1
PYPSF32		

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier
Trade name : Pyroil™ POWER STEERING FLUID

Relevant identified uses of the substance or mixture and uses advised against

Details of the supplier of the safety data sheet Niteo Products, LLC P.O. Box 191629 Dallas TX 75219 United States of America	Emergency telephone number CHEMTREC DIRECT 1-800-424-9300 Product Information 1-844-696-4836
--	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification
Reproductive toxicity : Category 2

GHS label elements
Hazard pictograms :



Signal Word : Warning

Hazard Statements : Suspected of damaging fertility or the unborn child.

Precautionary Statements : **Prevention:**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
IF exposed or concerned: Get medical advice/ attention.
Storage:
Store locked up.
Disposal:
Dispose of contents/ container to an approved waste disposal plant.

SAFETY DATA SHEET

Revision Date: 01/26/2016

Print Date: 2/21/2017

SDS Number: 000000264507

Pyroil™ POWER STEERING FLUID

Version: 1.1

PYPSF32

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	12.4183
TRICRESYL PHOSPHATE	1330-78-5	Acute Tox. 4; H332 Repr. 2; H361	0.2185

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.
If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs

		Page: 3
	SAFETY DATA SHEET	Revision Date: 01/26/2016
		Print Date: 2/21/2017
		SDS Number: 000000264507
Pyroil™ POWER STEERING FLUID		Version: 1.1
PYPSF32		

(i.e. lipid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
 stomach or intestinal upset (nausea, vomiting, diarrhea)
 irritation (nose, throat, airways)
 Suspected of damaging fertility or the unborn child.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Water spray
 Foam
 Carbon dioxide (CO2)
 Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
 Hydrocarbons

Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

SAFETY DATA SHEET

Revision Date: 01/26/2016

Print Date: 2/21/2017

SDS Number: 000000264507

Pyroil™ POWER STEERING FLUID
PYPSF32

Version: 1.1

- Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8			ACGIH
				ACGIHLIS_P
				ACGIHLIS_P
		REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3 Mist.	NIOSH/GUID E
		PEL	5 mg/m3	OSHA_TRA

		Page: 5
SAFETY DATA SHEET		Revision Date: 01/26/2016
		Print Date: 2/21/2017
		SDS Number: 000000264507
Pyroil™ POWER STEERING FLUID		Version: 1.1
PYPSF32		

			Mist.	NS
--	--	--	-------	----

Hazardous components without workplace control parameters

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection
Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

: Wear as appropriate:
Impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures

: Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : liquid
- Odour : No data available
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : No data available

SAFETY DATA SHEET

Revision Date: 01/26/2016

Print Date: 2/21/2017

SDS Number: 000000264507

Pyroil™ POWER STEERING FLUID

Version: 1.1

PYPSF32

Flash point	: > 390 °F / > 199 °C Method: Cleveland open cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: 1.33 hPa Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: No data available
Density	: No data available
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 42 mm ² /s (40 °C)
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.
Conditions to avoid	: excessive heat
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition	

		Page: 7
	SAFETY DATA SHEET	Revision Date: 01/26/2016
		Print Date: 2/21/2017
		SDS Number: 000000264507
Pyroil™ POWER STEERING FLUID		Version: 1.1
PYPSF32		

products

carbon dioxide and carbon monoxide
Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

TRICRESYL PHOSPHATE:

Acute oral toxicity : LD50 (Rat, male and female): > 20,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): > 11.1 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Assessment: The component/mixture is classified as acute inhalation toxicity, category 5.
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit, male and female): 3,700 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Mildly irritating to skin

TRICRESYL PHOSPHATE:

Species: Rabbit

Exposure time: 4 h

Result: Slightly irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Mildly irritating to eyes

TRICRESYL PHOSPHATE:

Species: Rabbit

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

		Page: 8
SAFETY DATA SHEET		Revision Date: 01/26/2016
		Print Date: 2/21/2017
		SDS Number: 000000264507
Pyroil™ POWER STEERING FLUID		Version: 1.1
PYPSF32		

Respiratory sensitisation: Not classified based on available information.

Components:

TRICRESYL PHOSPHATE:

Test Type: Local lymph node assay

Exposure routes: Dermal

Species: Mouse

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 429

GLP: yes

Germ cell mutagenicity

Not classified based on available information.

Components:

TRICRESYL PHOSPHATE:

Genotoxicity in vitro

: Test Type: Chromosome aberration test in vitro
 Test species: Chinese hamster lung cells
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
 Result: negative
 GLP: yes

: Test Type: Ames test
 Test species: Salmonella typhimurium
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 471
 Result: negative
 GLP: no

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:

TRICRESYL PHOSPHATE:

Effects on fertility

: Test Type: Fertility/early embryonic development
 Species: Rat, male and female
 Application Route: Oral

Test Type: Two-generation study
 Species: Mouse, male and female
 Application Route: Oral

Effects on foetal development

: Test Type: Embryo-foetal development
 Species: Rat, male and female
 Application Route: Oral
 Method: OPPTS 870.3700
 Result: Teratogenic potential
 GLP: yes

Reproductive toxicity - Assessment

: Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

		Page: 9
SAFETY DATA SHEET		Revision Date: 01/26/2016
		Print Date: 2/21/2017
		SDS Number: 000000264507
Pyroil™ POWER STEERING FLUID		Version: 1.1
PYPSF32		

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Chronic aquatic toxicity : Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

Components:

TRICRESYL PHOSPHATE:

Toxicity to fish : LC50 (Rainbow darter (*Etheostoma caeruleum*)): 0.6 mg/l
Exposure time: 96 h
Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : (*Daphnia magna* (Water flea)): 0.146 mg/l
Test Type: Immobilization
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae : ErC50 (*Pseudokirchneriella subcapitata* (microalgae)): > 2.5 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

Revision Date: 01/26/2016

Print Date: 2/21/2017

SDS Number: 000000264507

Pyroil™ POWER STEERING FLUID

Version: 1.1

PYPSF32

Test Type: Growth inhibition
 Method: OECD Test Guideline 201
 GLP: yes

M-Factor (Acute aquatic toxicity) : 1

Toxicity to fish (Chronic toxicity) : (Oncorhynchus mykiss (rainbow trout)): 0.9 mg/l
 Exposure time: 28 d

Toxicity to bacteria : EC 50 (activated sludge): > 1,000 mg/l
 Exposure time: 3 h
 Test Type: Respiration inhibition
 Method: OECD Test Guideline 209
 GLP: yes

Ecotoxicology Assessment
 Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Persistence and degradability

TRICRESYL PHOSPHATE:

Biodegradability : Result: Readily biodegradable
 Biodegradation: 80 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301C
 GLP: yes

No data available

Bioaccumulative potential

TRICRESYL PHOSPHATE:

Bioaccumulation : Species: Fathead minnow (Pimephales promelas)
 Bioconcentration factor (BCF): 165
 Exposure time: 32 d
 Concentration: 0.0316 mg/l
 Method: Flow through

Partition coefficient: n-octanol/water : log Pow: 5.93

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

SAFETY DATA SHEET

Revision Date: 01/26/2016

Print Date: 2/21/2017

SDS Number: 000000264507

Pyroil™ POWER STEERING FLUID
PYPSF32

Version: 1.1

- General advice : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
- Dispose of in accordance with all applicable local, state and federal regulations.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

SAFETY DATA SHEET

Revision Date: 01/26/2016

Print Date: 2/21/2017

SDS Number: 000000264507

Pyroil™ POWER STEERING FLUID

Version: 1.1

PYPSF32

Not dangerous goods	MARINE POLLUTANT:(TRICRESYL PHOSPHATE, TRI-ORTHO- CRESYL PHOSPHATE)
---------------------	--

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant		yes
------------------	--	-----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

- SARA 311/312 Hazards** : Chronic Health Hazard
- SARA 313 Component(s)SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
- California Prop 65** : Proposition 65 warnings are not required for this product based on the results of a risk assessment.
- The components of this product are reported in the following inventories:**
- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory

NITEO PRODUCTS		Page: 13
SAFETY DATA SHEET		Revision Date: 01/26/2016
		Print Date: 2/21/2017
		SDS Number: 000000264507
Pyroil™ POWER STEERING FLUID		Version: 1.1
PYPSF32		

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 01/26/2016

NFPA:	HMIS III:						
<p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard.</p>	<table border="1"> <tr> <td>HEALTH</td> <td>0*</td> </tr> <tr> <td>FLAMMABILITY</td> <td>1</td> </tr> <tr> <td>PHYSICAL HAZARD</td> <td>0</td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	0*	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	0*						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

- H304 May be fatal if swallowed and enters airways.
- H332 Harmful if inhaled.
- H361 Suspected of damaging fertility or the unborn child.

Sources of key data used to compile the Safety Data Sheet

Internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

Cefic, the European Chemical Industry Council.

ESIS European Chemical Substances Information System

		Page: 14
SAFETY DATA SHEET		Revision Date: 01/26/2016
		Print Date: 2/21/2017
		SDS Number: 000000264507
Pyroil™ POWER STEERING FLUID		Version: 1.1
PYPSF32		

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Niteo's Environmental Health and Safety Department (1-844-696-4836).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
 BEI : Biological Exposure Index
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
 FG : Food grade
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
 H-statement : Hazard Statement
 IATA : International Air Transport Association.
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
 DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
 WHMIS : Workplace Hazardous Materials Information System